

A method of flooring using butting panels fixed to a frame primarily of joists, joints transverse of the longitudinal axes of the joists being largely unnogged. To support such joints unsupported by a framing element reliance is placed on panel edge to panel edge adhesion. In a preferred form particle board panels each provided with an edge groove have the effect of ensuring both a sufficient availability of adhesive for an effective butt joint whilst, in addition, providing a keying or splining between the adjacent panels.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**“A FLOORING PANEL AND/OR FLOORING OF SUCH FLOORING  
PANELS AND/OR RELATED METHODS”**

**TECHNICAL FIELD**

5       The present invention relates to flooring panels, flooring provided by such panels, methods of providing a floor, flooring thus provided and panels for use in such a method.

      Panels for flooring are usually (but not necessarily) made of a reconstituted material which includes wood fibres. Examples include particle board, plywood and  
10 other fibre boards. Typical of such materials used as flooring panels are KOPINE™ panels of this company which is a high density particle board. Other suitable materials for such flooring may include the PYNEFLOOR™ particle board product of Fletcher Wood Panels.

      Prior art flooring procedures where flooring planks or panels are to be used  
15 have involved the extensive use of nogs between the joists of the flooring frame. Such complex suspended flooring frames are time consuming and costly. Timber nogs are not without a material cost and also take time to measure, cut and nail in place.

      Over a period of time nogs can give uneven support of an overlying panel  
20 owing to drying or warping, thus eventually allowing movement and squeaking.

      With such complex nog including suspended floor frames it is usual to abut the edges of the panels on a joist, some peripheral timber member or a nog and to attach the panel by appropriate penetrative means (eg. nails, screws or the like) or adhesive or both.

25       A variant on the abutment of straight cut edge panels is a tongue and groove type insert engagement of a kind that traditionally was used with timber planks. Such arrangements however involve the exposure to potential damage (prior to fitment) of the tongues and grooves. There is also a need to match male with female edges.

## DISCLOSURE OF INVENTION

The present invention recognises economies of material, time and money that can arise if there is evolved a satisfactory system using flooring panels less susceptible to panel edge damage yet which can be fixed to a suspended floor frame primarily of joists without a need or any significant need for nogs under abutments of panels which are to run perpendicular to the run of the joists. It is therefore an object of the present invention to provide panels, methods and flooring which at least provides some of the aforementioned advantages.

In a first aspect the present invention consists in a **method of edgewise joining flooring panels** which comprises positioning a first panel on a flooring frame including joists, said panel having an edge (preferably provided with at least one groove), which edge does not run along the longitudinal axis of a joist, and positioning a second panel on the flooring frame having an edge (preferably provided with at least one groove complementary to that of said first panel), wherein said method includes the additional steps of applying adhesive to at least one of said (preferably grooved) edges and then bringing the panels substantially together prior to fixing or allowing the fixing of the panels or the second panel to the frame, the adhesive being applied in such a way and being of a kind whereby there is an adhesive joint having a resistance in shear to relative vertical movement of the panel edges (as well as preferably a forming of a spline between the panels moulded at least in part by the preferred said complementary grooves).

In some forms a non grooved square edge may be utilised. In other forms grooves and/or holes and/or depressions in such edges may be provided.

Preferably said panels are each of a composite which includes wood fibre material or at least included wood fibre material.

Preferably said first panel is fixed prior to the positioning and fixing of the second panel.

Preferably the fixing of each panel comprises or includes nailing and/or screwing into said joists.

Preferably the panel to panel adhered and adhesive formed splined joint does

not overlie nogs.

Preferably said panels are rectangular and are grooved on two opposed sides only, such sides being normal to the run of the joists.

Preferably said panels are rectangular and at least the two longer sides are  
5 grooved.

Preferably those edges of panels to be adjacent the edges of other panels along a joist are ungrooved.

Preferably adhesive is applied to at least one edge of fixed panels prior to abutment thereagainst of a yet to be fixed panel.

10 Preferably the adhesive is of a solvent mastic type formulation with a synthetic rubber base. However other types of adhesive may be used, eg: epoxy or woodworking glues such as Resorcinol or PVA.

In another aspect the invention is a **floor** comprising a floor frame of primarily joists, and a plurality of abutting panels positioned on top of said floor frame to  
15 define the desired floor shape, adjacent edges of adjacent panels which are substantially perpendicular to the joist axes and are unsupported by nogs being fixed by adhesive one edge to another.

In another aspect the invention is a **method of edgewise joining flooring panels** which comprises fixing in place a first panel said panel having an edge  
20 provided with at least one groove, applying adhesive into said groove(s), and

abutting a second panel provided with at least one groove complementary to that of said first panel in the plane of the first panel,  
so that there is an adhesive joint having a resistance in shear to relative vertical movement of the panel edges as well as a forming of a spline between the panels  
25 moulded at least in part by the said complementary grooves.

In another aspect the invention is **flooring** or a **floor** formed by a method of the present invention.

In still a further aspect the present invention consists in a **flooring panel** useful in a method as previously set forth, said panel being of a composite form including  
30 wood fibre and having at least one grooved edge.

In another aspect the invention consists in a **flooring panel** in the form of a

rectangular or square sheet having a pair of opposite edges provided with at last one groove.

Preferably the groove is in a longer pair of edges.

Preferably said groove(s) is(are) centrally positioned on such edges.

5 In still a further aspect the present invention consists in a **floor** comprising a floor frame of primarily joists, and a plurality of abutting panels positioned on top of said floor frame to define the desired floor shape, at least part of each adjacent edge of adjacent panels which is substantially perpendicular to the joist axes is provided with a groove which complements a corresponding groove of the adjacent edge of  
10 the adjacent panel, a spline having been moulded in said complementary grooves during adhesive butting of said edges after adhesive has been applied to at least one of said edges, said adhesive being of a type which assumes a shape retaining form sufficient to serve a spline function in addition to any adhesive function it may provide.

15 In still a further aspect the present invention consists in a **floor** as just defined when formed by any method as previously defined.

### **BRIEF DESCRIPTION OF DRAWINGS**

Preferred forms of the present invention will now be described with reference to the accompanying drawings in which

20 Figure 1 shows a flooring panel of a reconstituted material (eg; particle board) showing how it is positioned and fixed so that its perimeter can subsequently edgewise butt adjacent panels (not shown) from a number of directions over a support element which is either a joist or a nog,

Figure 2 shows how penetrative means such as nails or screws (shown in  
25 broken outline) may be used alone or in conjunction with adhesion to fix each peripheral region of butting flooring panels to either a joist or a nog,

Figures 3A, B and C show some options for a preferred rectangular panel of the present invention, Figure 3A showing a most preferred option where two groovings of edges of the flooring panel (preferably of a suitable particle board) is provided on  
30 the longer opposed pair of sides, Figure 3B showing an alternative where there is machining only on the shorter of the opposed pair of sides, and

Figure 3C showing where there is machining all around the panel (obviously there is the option of the provision of grooving on a single edge or a pair of adjacent edges only etc.),

Figure 4 is a cross section of a preferred flooring panel showing the nature of a preferred form of the groove provided therein,

Figure 5A shows a panel of the kind depicted in Figure 4 having a bead of glue applied into the groove of that panel that has already been fixed in place (or *vice versa* also being an option) and a like panel being brought into abutment therewith,

Figure 5B shows a variant where there is an application of a bead of adhesive in the grooves of both panels prior to the creation of the abutment,

Figure 6 is the outcome of a butting together of the panel edges by a procedure of either Figure 5A or Figure 5B, the dotted lines showing adhesive that is preferably squeezed from between the panels which at least in respect of the top edge can be easily scraped away,

Figure 7 is a similar view to that of Figure 4 but showing a different form of groove,

Figure 8 shows still a further variant reliant on multiple grooves,

Figure 9 shows still a further groove option,

Figure 10 shows panels of a kind as depicted in any of Figures 3A onwards being brought into abutment over some flooring joists without nogs underlying the line of joint, the edges being grooved,

Figure 11 shows how if desired a joist can underline mating panels which are free of any groove, the provision of an optional groove even at that line of abutment being depicted by the broken lines,

Figure 12 shows how in accordance with the present invention a suspended flooring frame primarily of joists can have a panel arranged to be fixed directly into the peripheral framing member and the joists and can present an edge for abutment along a joist and perpendicular to the joists without a need for nogs,

Figure 13 shows the region A of Figure 12,

Figure 14 shows how a panel such as depicted in Figure 12 and Figure 13 can butt against a like panel,

Figure 15 is a similar view to that of Figure 2 which was a prior art arrangement but showing in section the same type of arrangement but this time restricted to a joist, i.e. no nog being necessary, the broken lines showing this is the grooved panel form,

5        Figure 16 shows an arrangement whereby to provide lap a panel of a rectangular form as depicted in Figure 12 can be rotated by 90° at one part, the shorter edge in such an arrangement preferably being grooved or overlying a nog (not shown),

10        Figure 17 shows how if desired a joist can underlie a grooved edge of a panel in abutment with an already fixed panel,

Figure 18 shows a preferred form of flooring with the present invention a first panel having been fixed by both adhesion and screwing to present a grooved edge perpendicular to the joist run direction and a like panel being brought into abutment thereof,

15        Figure 19 showing how preferably a bead of suitable adhesive is provided on the preferably non-grooved edges for such butting over the joists,

Figure 20 shows the butting of the arrangement of Figure 19 with glue spill over which then indicates the appropriateness to then screw or nail home the panel into its fixed position,

20        Figure 21 shows how the overflow of adhesion from the joint is preferably removed,

Figure 22 shows how a similar grooved panel in a lapping relationship previously referred to can be fitted,

25        Figure 23 showing how a bead of adhesive is applied at least into the groove of the fixed and the panel then brought into the abutment to provide the effect as shown in Figures 20 and 21 for the non grooved abutment over the joist and a like arrangement to that of Figures 20 and 21 even for the grooved arrangement which results in the outcome as depicted in Figure 6, such outcome being the provision of an adhesive jointing of the panel edges to each other and the provision of an  
30        adhesive formed spline between the panels where such panels are not supported by nogs.



Figure 1 shows the prior art method of using floor panels. In such a method a floor panel 1 is usually fixed both by adhesive and nailing at at least its periphery on the suspended floor frame 2 which comprises at least joists 3 which run in parallel. In addition nogs 4, which must be cut for length and be positioned appropriately  
5 between adjacent joists 3, underlie the abutment edge of the panel 1 with the adjacent panel. The same procedure follows throughout the whole floor.

By reference to "abutment" with adjacent panels please appreciate that this term includes actual physical abutment panel to panel as well as abutment through an adhesive medium. In some instances "abutment" may mean close proximity but  
10 preferably it does mean actual physical edgewise touching panel to panel or indirect panel to panel touching through an adhesive joint providing adhesive layer.

Figure 2 shows the arrangement of the prior art panel looking along a joist 3 with one panel 1 abutting an adjacent panel 5 and being fixed into the joist 3 by appropriate nails or screws 6. The same procedure would be shown were one to look  
15 along the axis of a nog 4.

The present invention recognises that the expense and time involved in accurately positioning nogs so that every line of abutment between adjacent panels is on the axis of a framing member (whether it be a joist or nog) can be avoided. Since joists are preferably always present conventional abutment on the line of the joists  
20 can occur but to avoid the need for nogs preferably the jointing procedure of the present invention is adopted so as to provide for a resultant floor the requisite strength characteristics and without the likelihood of "squeaking" owing to nog shrinkage or skewing.

Flooring panels take a variety of different forms. A preferred form is that of a  
25 composite product including wood fibre typified by various commercially available panels as previously described. Within the ambit of such composite material are such products as particle board, MDF, plywood, etc.

Figure 3A through 3C shows a variety of different panels of a kind that it is envisaged can be manufactured in a factory and be supplied to a site for installation  
30 prior to there necessarily being any damage of consequence to the modified edges shown, ie; there are no easily damaged tongues.

In the panel of Figure 3A, the opposed longer edges 7 are each provided with grooving.

In the panel of Figure 3B the smaller opposed pair of sides 8 are instead grooved. Such a panel may have some application in assisting panel layout  
5 staggering to better tie a floor together.

Another form for the panel is as shown in Figure 3C where edges 9 and 10 are all grooved. Such a form of the panel however is more expensive than that of Figure 3A or Figure 3B since routing of the opposed edges during manufacture is not as simple where routing is required only to provide two opposed pairs of grooved sides.

10 Obviously forms of panel in accordance with the present invention can be provided which are grooved on one side only.

Still other forms of panel may be other than rectangular or indeed even square. There may well be structures where the floor frame is framing an area other than one which lends itself to rectangular or square panel forms in which case complex panels  
15 having curved, triangulated or other edges may be utilised. Even for such arrangements however, where there is to be abutment otherwise than on the line of a joist, the procedure of the present invention is believed to have application.

Preferably the edges as depicted in Figures 3A through 3C for a panel 11 are as shown in Figure 4 as 12.

20 Figure 5A shows how, for example, one panel (preferably already fixed) 13 may have a bead of appropriate liquid (yet viscous) adhesive 14 applied thereto prior to the complementary edge of a panel 15 being brought into engagement therewith so as to provide the abutment arrangement as shown in Figure 6 where the complementary grooves at least substantially shape at least a partial intermittent or  
25 continuous spline like structure upon the curing, hardening or the like of the adhesive, preferably also in conjunction with an adhesive interface between the non grooved edge regions of each panel.

Figure 5B is a variant of the arrangement of Figure 5A where in this form adhesive is applied into both grooved edges prior to their being brought into the  
30 abutment substantially as shown in Figure 6.

As can be seen (Figure 6) a spline like structure 16 results in addition to

preferably adhered regions 17. Overflow of the adhesive shown in dotted outline as 18 can easily be scraped away as shown, for example, in Figure 21 which shows a scraper 19.

Other forms of groove which adapt to complementary panels are those depicted  
5 in Figures 7 through 9. In each instance it is to be seen that irrespective of whether or not there is one or two grooves (indeed there might even be more) preferably the positioning of the grooves is such that does not matter which way up the panel is positioned. Should however a particular composite material have a surface that must be uppermost this symmetry of the groove provision is not mandatory. In such  
10 arrangement asymmetric positioning of a single or multiple grooves can be provided knowing that they will match and complement a similarly configured panel which likewise must also have a predetermined face uppermost.

Figure 10 shows an arrangement where parallel joists 3 support a first panel 20 thereon with its grooved edge 21 substantially normal to the run of the joists 3. Panel  
15 20 is to be abutted with a similar panel 22 which will move in the arrowed direction so as to bring its grooved edge into abutment (preferably through an interface of adhesive).

Figure 11 however shows how that edge 23 of a floor panel 20 need not be grooved although the broken lines in Figure 11 show that optionally (where a panel  
20 embodiment as shown, for example, 3C is used) that edge may also be grooved. In such a form as shown in Figure 11 despite nails, screws or the like preferably being used preferably also there is an application of adhesive between the complementary faces 23 and 24 much in the conventional way.

Thus Figure 12, in a manner as shown in Figure 1, shows the joists 3 are  
25 preferably not provided with any nogs and the vertical support for the panels on their grooved edges 25 and 26 is as described by reference to Figure 10 and as disclosed with reference to Figure 11.

Figure 13 shows how preferably a plurality of nails, screws or the like 27 are preferably provided along the periphery in conjunction with any application of  
30 adhesive on to the frames much in the conventional way.

Figure 14 in a manner similar to Figure 13 shows how an abutment of the kind

referred to in Figure 11 results. Figure 15, looking along the joist 3, shows how the adjacent panels 20 and 28 are fixed by screws, nails or the like into the joist 3.

Figure 16 shows how, if desired, a panel 29 of the kind depicted in either Figure 3B or 3C can be utilised with its major axis aligned differently the major axes of other panels (eg; panels 20 and 28) so as to ensure a panel yet to be laid with its major axis parallel to the major axes of panels 20 and 28 will lap over the joint region 30 if desired.

Figure 17 is a close up of the region 31 of Figure 16.

The preferred form of the present invention will now be described with respect to the installation sequence of Figures 18 through 23.

By way of example, KOPINE Ultralock™ particle board floor panels of this company of sheet size of either 2400 x 1200 x 20 mm or 3600 x 1200 x 20 mm are preferably used. KOPINE Ultralock™ particle board is a reconstituted wood panel manufactured by bonding pine wood particles with a melamine urea formaldehyde resin using a combination of heat and pressure. Such a particle board has average values when tested to AS/NZS 4266:1995 as follows;

	•	Density	kg/m <sup>3</sup>	710
	•	Internal Bond	kPa	900
20	•	Modulus of Rupture	MPa	22
	•	Modulus of Elasticity	MPa	3000
	•	Moisture Content	%	8
	•	Water Adsorption (one hour soak)	%	4
	•	Thickness Swell (one hour soak)	%	2
25		Surface - Flake finish.		

The adhesive preferably used in the procedure is any compatible spline forming adhesive preferably providable in a convenient cartridge size to fit a glue gun. An example of an appropriate adhesive is Fuller's Sturdibond™ Adhesive which is available in New Zealand. The adhesive is a solvent mastic type formulation with a synthetic rubber base and it is compatible with the KOPINE Ultralock™ composite

panel.

The panels are designed with the grooving as depicted to be laid across joists and glued together at the edges. The continuous glue bond of the edges that do not overlie the axis of a joist eliminates the need for further edge support such as timber  
5 nogging.

Preferably all end joints (ie; of the opposed preferably ungrooved shorter edges) are made over the axis of a joist and are glued together.

Preferably joists are no more than 600 mm apart. For even greater strength and stiffness however joists may be set at a spacing of, for example, 400 or 450 mm.

10 Preferably the panels are laid in a staggered brick like pattern as described such that there is lapping to tie the floor/floor frame as a racking resistant structure.

The application of the preferred glue is to the single groove of the preferred panel and it is supplied as a continuous run of about 5 mm bead diameter. The bead size is correct when the adhesive squeezes out of the joint (top and bottom) as the  
15 panels are pushed together. This is preferably the case whether or not one is applying adhesive to the joist supported edges or the edges preferably normal to the run of the joists. Preferably however more adhesive is to be available for the splined joints (which preferably run normal to the run of the joists).

It is desirable that the panels be fixed by appropriate nailing or screwing within  
20 15 minutes of the adhesive being applied.

Appropriate screws are 8-gauge x 50 mm Sure-fast™ type countersunk screws. Appropriate nails if to be hand driven) are 60 x 2.8 mm hot-dipped galvanised particle board nails. Power driven nails may also be used.

Adhesive fastening of the panels to the joists may be used alone or in  
25 conjunction with the penetrative fixing. If there is to be such adhesion down on to the framing members preferably a 10 mm bead of Fuller's Sturdibond™ is applied to the joists and a 5 mm bead to the panel edges prior to the panels being positioned.

The present invention recognises a desirability to reduce reliance on nogging in the provision of a floor supported by a floor frame. The present invention also by  
30 adopting the grooved edge feature in mated panels has enabled greater glue retention in the joint than is possible with straight square edged abutment. This enhanced glue

retention better copes with movement after laying prior to the glue being cured. In the long term such glue in the mated grooves provides the added security of a physical "key" or "spline" between the panels to augment the glue bond.

5       With the prospect that some tradesmen may have insufficient training or ability, the advantages offered by the grooved edges for gluing provides an added assurance that an effective bonded panel to panel joint will result. Even with such joints soon after cure of the bonding adhesive, greater consistency of performance over simple square edge adhesive joints results. There is also an improvement in resistance to failure under load in shear.

10       Persons skilled in the art will appreciate how the flooring thus laid after an appropriate setting time can then be finished to appropriate standard.

**CLAIMS:**

1. A method of edgewise joining flooring panels which comprises positioning a first panel on a flooring frame including joists, so as to reveal an edge which does not run along the longitudinal axis of a joist, and
  - 5 positioning a second panel on the flooring frame having an edge,  
wherein said method includes the additional steps of applying adhesive to at least one of said grooved edges and then bringing the panels substantially together prior to fixing or allowing the fixing of the panels or the second panel to the frame, the adhesive being applied in such a way and being of a kind whereby there is an  
10 adhesive joint having a resistance in shear to relative vertical movement of the panel edges.
  2. A method of claim 1 wherein said panels are each of a composite which includes wood fibre material or at least included wood fibre material.
  3. A method of claim 1 or 2 wherein said first panel is fixed prior to the  
15 positioning and fixing of the second panel.
  4. A method of any one of the preceding claims wherein the fixing of each panel comprises or includes nailing and/or screwing into said joists.
  5. A method of any one of the preceding claims wherein the panel to panel adhered and adhesive formed splined joint does not overlie nogs.
  - 20 6. A method of any one of the preceding claims wherein said edge of said first panel is grooved and said edge of said second panel is grooved thereby to result in the forming of a key or spline between the panels by the adhesive once set or cured reliant upon such grooves.
  7. A method of claim 6 wherein said panels are rectangular and are grooved on  
25 two opposed sides only, such two opposed sides being normal to the run of the joists.
  8. A method of claim 6 wherein said panels are rectangular and at least the two longer sides are grooved.
  9. A method of claim 8 wherein those edges of panels to be adjacent the edges of other panels along a joist are ungrooved.
  - 30 10. A method of any one of the preceding claims wherein adhesive is applied to at least one edge of fixed panels prior to abutment thereagainst of a yet to be fixed

panel.

11. A method of any one of the preceding claims wherein the adhesive is of a solvent mastic type formulation with a synthetic rubber base.

12. A method of edgewise joining flooring panels which comprises fixing in place  
5 a first panel said panel having an edge provided with at least one groove, applying adhesive into said groove(s), and

abutting a second panel provided with at least one groove complementary to that of said first panel in the plane of the first panel,

so that there is an adhesive joint having a resistance in shear to relative vertical  
10 movement of the panel edges as well as a forming of a spline between the panels moulded at least in part by the said complementary grooves.

13. Flooring or a floor formed by a method of any one of the preceding claims.

14. A flooring panel useful in a method of any one of claims 1 to 12, said panel being of a composite material including wood fibre or which included wood fibre as  
15 a raw material and having at least one grooved edge.

15. A flooring panel of claim 14 in the form of a rectangular or square sheet having a pair of opposite edges provided with at last one groove fully extensive with the length of each edge.

16. A panel of claim 15 wherein the groove is in a longer pair of edges.

20 17. A panel of claim 15 or 16 wherein said groove(s) is(are) centrally positioned on such edges.



18. A floor comprising a floor frame of primarily joists, and a plurality of abutting panels positioned on top of said floor frame to define the desired floor shape, at least part of each adjacent edge of adjacent panels which is substantially perpendicular to  
25 the joist axes is provided with a groove which complements a corresponding groove of the adjacent edge of the adjacent panel, a spline having been moulded in said complementary grooves during adhesive butting of said edges after adhesive has been applied to at least one of said edges, said adhesive being of a type which assumes a shape retaining form sufficient to serve a spline function in addition to  
30 any adhesive function it may provide.

19. A floor as claimed in claim 18 wherein said floor has been formed by a method



as claimed in any one of claims 1 to 13.

20. A floor comprising a floor frame of primarily joists, and a plurality of abutting panels positioned on top of said floor frame to define the desired floor shape, adjacent edges of adjacent panels which are substantially perpendicular to the joist axes and are unsupported by nogs being fixed by adhesive one edge to another.
21. A method flooring substantially as hereinbefore described with reference to the accompanying drawings.
22. Floor panels substantially as hereinbefore described with reference to the accompanying drawings.
23. A floor constructed by a method of claim 21.

FIG. 1FIG. 2




FIG. 3A





FIG. 3B






FIG. 4




FIG. 5A








FIG. 5B

FIG. 6FIG. 7FIG. 8FIG. 9







FIG. 11





FIG. 12FIG. 13



FIG. 14FIG. 15



FIG. 16FIG. 17



FIG. 18FIG. 19





FIG. 20FIG. 21

FIG. 22FIG. 23

**A. CLASSIFICATION OF SUBJECT MATTER**Int Cl<sup>6</sup>: E04F 15/02, E04B 5/02

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC: E04F 15/-, E04B/-

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

AU IPC: E04F 15/02, E04B 5/02

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPAT &amp; JAPIO + keywords (FLOOR:, PANEL, BOARD, SHEET, PLANK, ADHESIVE, GLUE, CEMENT, EDGE, SIDE, END ,ABUT:)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	JP 09209462 A (SEKISUI CHEM CO LTD) 12 August 1997	
A	JP 07189350 A (MISAWA HOMES CO LTD) 28 July 1995	
A	EP 123136 A2 (WERTHEBACH G) 31 October 1984	



Further documents are listed in the continuation of Box C



See patent family annex

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T"

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X"

document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y"

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;"

document member of the same patent family

Date of the actual completion of the international search

8 March 1999

Date of mailing of the international search report

19 MAR 1999

Name and mailing address of the ISA/AU

AUSTRALIAN PATENT OFFICE

PO BOX 200

WODEN ACT 2606

AUSTRALIA

Facsimile No.: (02) 6285 3929

Authorized officer

**GEOFF SADLIER**

Telephone No.: (02) 6283 2114

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International application No.  
**PCT/NZ 98/00162**

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report		Patent Family Member	
EP	123136	DE	3310280
END OF ANNEX			



(12) PATENT  
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 199886116 C**  
(10) Patent No. **724982**

(54) Title  
**A flooring panel and/or flooring of such flooring panels and/or related methods**

(51)<sup>7</sup> International Patent Classification(s)  
**E04B 001/38 E04C 002/16**  
**E04B 005/14 E04F 015/10**

(21) Application No: **199886116**

(22) Application Date: **1998.09.22**

(30) Priority Data

(31) Number	(32) Date	(33) Country
<b>329058</b>	<b>1997.10.28</b>	<b>NZ</b>
<b>330083</b>	<b>1998.03.30</b>	<b>NZ</b>

(43) Publication Date : **1999.05.20**

(43) Publication Journal Date : **1999.05.20**

(44) Accepted Journal Date : **2000.10.05**

(44) Amended Journal Date : **2001.10.25**

(71) Applicant(s)  
**Carter Holt Harvey Limited**

(72) Inventor(s)  
**Michael John Coup**

(74) Agent/Attorney  
**A J PARK and SON, Level 11, 60 Marcus-Clarke Street, CANBERRA ACT 2601**

(56) Related Art  
**AU 64802/74**  
**EP 147801**  
**FR 2399514**


*In Force*

**ABSTRACT:**

A method of edgewise joining flooring panels which comprises positioning a first panel on a flooring frame including joists, said panel having an edge provided with at least one groove, which edge does not run along the longitudinal axis of a joist, and

positioning a second panel on the flooring frame having an edge provided with at least one groove complementary to that of said first panel,

wherein said method includes the additional steps of applying adhesive to at least one of said grooved edges and then bringing the panels substantially together prior to fixing or allowing the fixing of the panels or the second panel to the frame, the adhesive being applied in such a way and being of a kind whereby there is an adhesive joint having a resistance in shear to relative vertical movement of the panel edges as well as a forming of a spline between the panels moulded at least in part by the said complementary grooves.



AUSTRALIA  
Patents Act 1990

**COMPLETE SPECIFICATION**  
**STANDARD PATENT**

**Applicant(s):**

CARTER HOLT HARVEY LIMITED

**Invention Title:**

A FLOORING PANEL AND/OR FLOORING OF SUCH FLOORING PANELS AND/OR  
RELATED METHODS

The following statement is a full description of this  
invention, including the best method of performing it known to  
me/us:

---

The present invention relates to flooring panels, flooring provided by such panels, methods of providing a floor, flooring thus provided and panels for use in such a method.

Panels for flooring are usually (but not necessarily) made of a reconstituted material which includes wood fibres. Examples include particle board, plywood and other fibre boards. Typical of such materials used as flooring panels are KOPINE™ panels of this company which is a high density particle board. Other suitable materials for such flooring may include the PYNEFLOOR™ particle board product of Fletcher Wood Panels.

Prior art flooring procedures where flooring planks or panels are to be used have involved the extensive use of nogs between the joists of the flooring frame. Such complex suspended flooring frames are time consuming and costly. Timber nogs are not without a material cost and also take time to measure, cut and nail in place.

Over a period of time nogs can give uneven support of an overlying panel owing to drying or warping, thus eventually allowing movement and squeaking.

With such complex nog including suspended floor frames it is usual to abut the edges of the panels on a joist, some peripheral timber member or a nog and to attach the panel by appropriate penetrative means (eg. nails, screws or the like) or adhesive or both.

A variant on the abutment of straight out edge panels is a tongue and groove type insert engagement of a kind that traditionally was used with timber planks. Such arrangements however involve the exposure to potential damage (prior to fitment) of the tongues and grooves. There is also a need to match male with female edges.

The present invention recognises economies of material, time and money that can arise if there is evolved a satisfactory system using flooring panels less susceptible to panel edge damage yet which can be fixed to a suspended floor frame primarily of joists without a need or any significant need for nogs under abutments of panels which are to run perpendicular to the run of the joists. It is therefore an object of the present invention to provide panels, methods and flooring which at least provides some of the aforementioned advantages.

In a first aspect the present invention consists in a method of edgewise joining flooring panels which comprises positioning a first panel on a flooring frame including joists, said panel having an edge provided with at least one groove, which edge does not run along the longitudinal axis of a joist, and

positioning a second panel on the flooring frame having an edge provided with at least one groove complementary to that of said first panel,

wherein said method includes the additional steps of applying adhesive to at

least one of said grooved edges and then bringing the panels substantially together prior to fixing or allowing the fixing of the panels or the second panel to the frame, the adhesive being applied in such a way and being of a kind whereby there is an adhesive joint having a resistance in shear to relative vertical movement of the panel edges as well as a forming of a spline between the panels moulded at least in part by the said complementary grooves.

Preferably said panels are each of a composite which includes wood fibre material or at least included wood fibre material.

Preferably said first panel is fixed prior to the positioning and fixing of the second panel.

Preferably the fixing of each panel comprises or includes nailing and/or screwing into said joists.

Preferably the panel to panel adhered and adhesive formed splined joint does not overlie nogs.

Preferably said panels are rectangular and are grooved on two opposed sides only, such sides being normal to the run of the joists.

Preferably said panels are rectangular and at least the two longer sides are grooved.

Preferably those edges of panels to be adjacent the edges of other panels along a joist are ungrooved.

Preferably adhesive is applied to at least one edge of fixed panels prior to abutment thereagainst of a yet to be fixed panel.

Preferably the adhesive is of a solvent mastic type formulation with a synthetic rubber base. However other types of adhesive may be used, eg: epoxy or woodworking glues such as Resorcinol or PVA.

In another aspect the invention is a method of edgewise joining flooring panels which comprises fixing in place a first panel said panel having an edge provided with at least one groove, applying adhesive into said groove(s), and

abutting a second panel provided with at least one groove complementary to that of said first panel in the plane of the first panel,

so that there is an adhesive joint having a resistance in shear to relative vertical movement of the panel edges as well as a forming of a spline between the panels moulded at least in part by the said complementary grooves.

In another aspect the invention is flooring or a floor formed by a method of the present invention.

In still a further aspect the present invention consists in a flooring panel useful in a method as previously set forth, said panel being of a composite form including

wood fibre and having at least one grooved edge.

In another aspect the invention consists in a flooring panel in the form of a rectangular or square sheet having a pair of opposite edges provided with at least one groove.

Preferably the groove is in a longer pair of edges.

Preferably said groove(s) is(are) centrally positioned on such edges.

In still a further aspect the present invention consists in a floor comprising a floor frame of primarily joists, and a plurality of abutting panels positioned on top of said floor frame to define the desired floor shape, at least part of each adjacent edge of adjacent panels which is substantially perpendicular to the joist axes is provided with a groove which complements a corresponding groove of the adjacent edge of the adjacent panel, a spline having been moulded in said complementary grooves during adhesive butting of said edges after adhesive has been applied to at least one of said edges, said adhesive being of a type which assumes a shape retaining form sufficient to serve a spline function in addition to any adhesive function it may provide.

In still a further aspect the present invention consists in a floor as just defined when formed by any method as previously defined.

Preferred forms of the present invention will now be described with reference to the accompanying drawings in which

Figure 1 shows a flooring panel of a reconstituted material (eg; particle board) showing how it is positioned and fixed so that its perimeter can subsequently edgewise butt adjacent panels (not shown) from a number of directions over a support element which is either a joist or a nog,

Figure 2 shows how penetrative means such as nails or screws (shown in broken outline) may be used alone or in conjunction with adhesion to fix each peripheral region of butting flooring panels to either a joist or a nog,

Figures 3A, B and C show some options for a preferred rectangular panel of the present invention, Figure 3A showing a most preferred option where two groovings of edges of the flooring panel (preferably of a suitable particle board) is provided on the longer opposed pair of sides, Figure 3B showing an alternative where there is machining only on the shorter of the opposed pair of sides, and

Figure 3C showing where there is machining all around the panel (obviously there is the option of the provision of grooving on a single edge or a pair of adjacent edges only etc.),

Figure 4 is a cross section of a preferred flooring panel showing the nature of a preferred form of the groove provided therein,

Figure 5A shows a panel of the kind depicted in Figure 4 having a bead of glue

wood fibre and having at least one grooved edge.

In another aspect the invention consists in a flooring panel in the form of a rectangular or square sheet having a pair of opposite edges provided with at least one groove.

Preferably the groove is in a longer pair of edges.

Preferably said groove(s) is(are) centrally positioned on such edges.

In still a further aspect the present invention consists in a floor comprising a floor frame of primarily joists, and a plurality of abutting panels positioned on top of said floor frame to define the desired floor shape, at least part of each adjacent edge of adjacent panels which is substantially perpendicular to the joist axes is provided with a groove which complements a corresponding groove of the adjacent edge of the adjacent panel, a spline having been moulded in said complementary grooves during adhesive butting of said edges after adhesive has been applied to at least one of said edges, said adhesive being of a type which assumes a shape retaining form sufficient to serve a spline function in addition to any adhesive function it may provide.

In still a further aspect the present invention consists in a floor as just defined when formed by any method as previously defined.

Preferred forms of the present invention will now be described with reference to the accompanying drawings in which

Figure 1 shows a flooring panel of a reconstituted material (eg; particle board) showing how it is positioned and fixed so that its perimeter can subsequently edgewise butt adjacent panels (not shown) from a number of directions over a support element which is either a joist or a nog,

Figure 2 shows how penetrative means such as nails or screws (shown in broken outline) may be used alone or in conjunction with adhesion to fix each peripheral region of butting flooring panels to either a joist or a nog;

Figures 3A, B and C show some options for a preferred rectangular panel of the present invention, Figure 3A showing a most preferred option where two groovings of edges of the flooring panel (preferably of a suitable particle board) is provided on the longer opposed pair of sides, Figure 3B showing an alternative where there is machining only on the shorter of the opposed pair of sides, and

Figure 3C showing where there is machining all around the panel (obviously there is the option of the provision of grooving on a single edge or a pair of adjacent edges only etc.),

Figure 4 is a cross section of a preferred flooring panel showing the nature of a preferred form of the groove provided therein,

Figure 5A shows a panel of the kind depicted in Figure 4 having a bead of glue

applied into the groove of that panel that has already been fixed in place (or *vice versa* also being an option) and a like panel being brought into abutment therewith,

Figure 5B shows a variant where there is an application of a bead of adhesive in the grooves of both panels prior to the creation of the abutment,

Figure 6 is the outcome of a butting together of the panel edges by a procedure of either Figure 5A or Figure 5B, the dotted lines showing adhesive that is preferably squeezed from between the panels which at least in respect of the top edge can be easily scraped away,

Figure 7 is a similar view to that of Figure 4 but showing a different form of groove,

Figure 8 shows still a further variant reliant on multiple grooves,

Figure 9 shows still a further groove option,

Figure 10 shows panels of a kind as depicted in any of Figures 3A onwards being brought into abutment over some flooring joists without nogs underlying the line of joint, the edges being grooved,

Figure 11 shows how if desired a joist can underline mating panels which are free of any groove, the provision of an optional groove even at that line of abutment being depicted by the broken lines,

Figure 12 shows how in accordance with the present invention a suspended flooring frame primarily of joists can have a panel arranged to be fixed directly into the peripheral framing member and the joists and can present an edge for abutment along a joist and perpendicular to the joists without a need for nogs,

Figure 13 shows the region A of Figure 12,

Figure 14 shows how a panel such as depicted in Figure 12 and Figure 13 can butt against a like panel,

Figure 15 is a similar view to that of Figure 2 which was a prior art arrangement but showing in section the same type of arrangement but this time restricted to a joist, i.e. no nog being necessary, the broken lines showing this is the grooved panel form,

Figure 16 shows an arrangement whereby to provide lap a panel of a rectangular form as depicted in Figure 12 can be rotated by 90° at one part, the shorter edge in such an arrangement preferably being grooved or overlying a nog (not shown),

Figure 17 shows how if desired a joist can underlie a grooved edge of a panel in abutment with an already fixed panel,

Figure 18 shows a preferred form of flooring with the present invention a first panel having been fixed by both adhesion and screwing to present a grooved edge perpendicular to the joist run direction and a like panel being brought into abutment thereof,



Figure 19 showing how preferably a bead of suitable adhesive is provided on the preferably non-grooved edges for such butting over the joists,

Figure 20 shows the butting of the arrangement of Figure 19 with glue spill over which then indicates the appropriateness to then screw or nail home the panel into its fixed position,

Figure 21 shows how the overflow of adhesion from the joint is preferably removed,

Figure 22 shows how a similar grooved panel in a lapping relationship previously referred to can be fitted,

Figure 23 showing how a bead of adhesive is applied at least into the groove of the fixed and the panel then brought into the abutment to provide the effect as shown in Figures 20 and 21 for the non grooved abutment over the joist and a like arrangement to that of Figures 20 and 21 even for the grooved arrangement which results in the outcome as depicted in Figure 6, such outcome being the provision of an adhesive jointing of the panel edges to each other and the provision of an adhesive formed spline between the panels where such panels are not supported by nogs.

Figure 1 shows the prior art method of using floor panels. In such a method a floor panel 1 is usually fixed both by adhesive and nailing at at least its periphery on the suspended floor frame 2 which comprises at least joists 3 which run in parallel. In addition nogs 4, which must be cut for length and be positioned appropriately between adjacent joists 3, underlie the abutment edge of the panel 1 with the adjacent panel. The same procedure follows throughout the whole floor.

By reference to "abutment" with adjacent panels please appreciate that this term includes actual physical abutment panel to panel as well as abutment through an adhesive medium. In some instances "abutment" may mean close proximity but preferably it does mean actual physical edgewise touching panel to panel or indirect panel to panel touching through an adhesive joint providing adhesive layer.

Figure 2 shows the arrangement of the prior art panel looking along a joist 3 with one panel 1 abutting an adjacent panel 5 and being fixed into the joist 3 by appropriate nails or screws 6. The same procedure would be shown were one to look along the axis of a nog 4.

The present invention recognises that the expense and time involved in accurately positioning nogs so that every line of abutment between adjacent panels is on the axis of a framing member (whether it be a joist or nog) can be avoided. Since joists are preferably always present conventional abutment on the line of the joists can occur but to avoid the need for nogs preferably the jointing procedure of the present invention is adopted so as to provide for a resultant floor the requisite strength

characteristics and without the likelihood of "squeaking" owing to nog shrinkage or skewing.

Flooring panels take a variety of different forms. A preferred form is that of a composite product including wood fibre typified by various commercially available panels as previously described. Within the ambit of such composite material are such products as particle board, MDF, plywood, etc.

Figure 3A through 3C shows a variety of different panels of a kind that it is envisaged can be manufactured in a factory and be supplied to a site for installation prior to there necessarily being any damage of consequence to the modified edges shown, ie; there are no easily damaged tongues.

In the panel of Figure 3A, the opposed longer edges 7 are each provided with grooving.

In the panel of Figure 3B the smaller opposed pair of sides 8 are instead grooved. Such a panel may have some application in assisting panel layout staggering to better tie a floor together.

Another form for the panel is as shown in Figure 3C where edges 9 and 10 are all grooved. Such a form of the panel however is more expensive than that of Figure 3A or Figure 3B since routing of the opposed edges during manufacture is not as simple where routing is required only to provide two opposed pairs of grooved sides.

Obviously forms of panel in accordance with the present invention can be provided which are grooved on one side only.

Still other forms of panel may be other than rectangular or indeed even square. There may well be structures where the floor frame is framing an area other than one which lends itself to rectangular or square panel forms in which case complex panels having curved, triangulated or other edges may be utilised. Even for such arrangements however, where there is to be abutment otherwise than on the line of a joist, the procedure of the present invention is believed to have application.

Preferably the edges as depicted in Figures 3A through 3C for a panel 11 are as shown in Figure 4 as 12.

Figure 5A shows how, for example, one panel (preferably already fixed) 13 may have a bead of appropriate liquid (yet viscous) adhesive 14 applied thereto prior to the complementary edge of a panel 15 being brought into engagement therewith so as to provide the abutment arrangement as shown in Figure 6 where the complementary grooves at least substantially shape at least a partial intermittent or continuous spline like structure upon the curing, hardening or the like of the adhesive, preferably also in conjunction with an adhesive interface between the non grooved edge regions of each panel.

Figure 5B is a variant of the arrangement of Figure 5A where in this form adhesive is applied into both grooved edges prior to their being brought into the abutment substantially as shown in Figure 6.

As can be seen (Figure 6) a spline like structure 16 results in addition to preferably adhered regions 17. Overflow of the adhesive shown in dotted outline as 18 can easily be scraped away as shown, for example, in Figure 21 which shows a scraper 19.

Other forms of groove which adapt to complementary panels are those depicted in Figures 7 through 9. In each instance it is to be seen that irrespective of whether or not there is one or two grooves (indeed there might even be more) preferably the positioning of the grooves is such that does not matter which way up the panel is positioned. Should however a particular composite material have a surface that must be uppermost this symmetry of the groove provision is not mandatory. In such arrangement asymmetric positioning of a single or multiple grooves can be provided knowing that they will match and complement a similarly configured panel which likewise must also have a predetermined face uppermost.

Figure 10 shows an arrangement where parallel joists 3 support a first panel 20 thereon with its grooved edge 21 substantially normal to the run of the joists 3. Panel 20 is to be abutted with a similar panel 22 which will move in the arrowed direction so as to bring its grooved edge into abutment (preferably through an interface of adhesive).

Figure 11 however shows how that edge 23 of a floor panel 20 need not be grooved although the broken lines in Figure 11 show that optionally (where a panel embodiment as shown, for example, 3C is used) that edge may also be grooved. In such a form as shown in Figure 11 despite nails, screws or the like preferably being used preferably also there is an application of adhesive between the complementary faces 23 and 24 much in the conventional way.

Thus Figure 12, in a manner as shown in Figure 1, shows the joists 3 are preferably not provided with any nogs and the vertical support for the panels on their grooved edges 25 and 26 is as described by reference to Figure 10 and as disclosed with reference to Figure 11.

Figure 13 shows how preferably a plurality of nails, screws or the like 27 are preferably provided along the periphery in conjunction with any application of adhesive on to the frames much in the conventional way.

Figure 14 in a manner similar to Figure 13 shows how an abutment of the kind referred to in Figure 11 results. Figure 15, looking along the joist 3, shows how the adjacent panels 20 and 28 are fixed by screws, nails or the like into the joist 3.

Figure 16 shows how, if desired, a panel 29 of the kind depicted in either Figure 3B or 3C can be utilised with its major axis aligned differently the major axes of other panels (eg; panels 20 and 28) so as to ensure a panel yet to be laid with its major axis parallel to the major axes of panels 20 and 28 will lap over the joint region 30 if desired.

Figure 17 is a close up of the region 31 of Figure 16.

The preferred form of the present invention will now be described with respect to the installation sequence of Figures 18 through 23.

By way of example, KOPINE Ultralock™ particle board floor panels of this company of sheet size of either 2400 x 1200 x 20 mm or 3600 x 1200 x 20 mm are preferably used. KOPINE Ultralock™ particle board is a reconstituted wood panel manufactured by bonding pine wood particles with a melamine urea formaldehyde resin using a combination of heat and pressure. Such a particle board has average values when tested to AS/NZS 4266:1995 as follows;

• Density	kg/m <sup>3</sup>	710
• Internal Bond	kPa	900
• Modulus of Rupture	MPa	22
• Modulus of Elasticity	MPa	3000
• Moisture Content	%	8
• Water Adsorption (one hour soak)	%	4
• Thickness Swell (one hour soak)	%	2

Surface - Flako finish.

The adhesive preferably used in the procedure is any compatible spline forming adhesive preferably providable in a convenient cartridge size to fit a glue gun. An example of an appropriate adhesive is Fuller's Sturdibond™ Adhesive which is available in New Zealand. The adhesive is a solvent mastic type formulation with a synthetic rubber base and it is compatible with the KOPINE Ultralock™ composite panel.

The panels are designed with the grooving as depicted to be laid across joists and glued together at the edges. The continuous glue bond of the edges that do not overlie the axis of a joist eliminates the need for further edge support such as timber nogging.

Preferably all end joints (ie; of the opposed preferably ungrooved shorter edges) are made over the axis of a joist and are glued together.

Preferably joists are no more than 600 mm apart. For even greater strength and

stiffness however joists may be set at a spacing of, for example, 400 or 450 mm.

Preferably the panels are laid in a staggered brick like pattern as described such that there is lapping to tie the floor/floor frame as a racking resistant structure.

The application of the preferred glue is to the single groove of the preferred panel and it is supplied as a continuous run of about 5 mm bead diameter. The bead size is correct when the adhesive squeezes out of the joint (top and bottom) as the panels are pushed together. This is preferably the case whether or not one is applying adhesive to the joist supported edges or the edges preferably normal to the run of the joists. Preferably however more adhesive is to be available for the splined joints (which preferably run normal to the run of the joists).

It is desirable that the panels be fixed by appropriate nailing or screwing within 15 minutes of the adhesive being applied.

Appropriate screws are 8-gauge x 50 mm Sure-fast™ type countersunk screws. Appropriate nails if to be hand driven) are 60 x 2.8 mm hot-dipped galvanised particle board nails. Power driven nails may also be used.

Adhesive fastening of the panels to the joists may be used alone or in conjunction with the penetrative fixing. If there is to be such adhesion down on to the framing members preferably a 10 mm bead of Fuller's Sturdibond™ is applied to the joists and a 5 mm bead to the panel edges prior to the panels being positioned.

Persons skilled in the art will appreciate how the flooring thus laid after an appropriate setting time can then be finished to appropriate standard.

In the claims which follow and in the preceding description of the invention, except where the context requires otherwise due to express language or necessary implication, the word "comprising" is used in the sense of "including", i.e. the features specified may be associated with further features in various embodiments of the invention.

### WHAT WE CLAIM IS:

1. A method of edgewise joining flooring panels which comprises positioning a first panel on a flooring frame including joists, said panel having an edge provided with at least one groove, which edge does not run along the longitudinal axis of a joist, and

positioning a second panel on the flooring frame having an edge provided with at least one groove complementary to that of said first panel, wherein said method includes the additional steps of applying adhesive to at least one of said grooved edges and then bringing the panels substantially together prior to fixing or allowing the fixing of the panels or the second panel to the frame, the adhesive being applied in such a way and being of a kind whereby there is an adhesive joint having a resistance in shear to relative vertical movement of the panel edges as well as a forming of a spline between the panels moulded at least in part by the said complementary grooves, said adhesive being of a type which assumes a shape retaining form sufficient to serve a spline function in addition to any adhesive function it may provide, and at least some adhesive has set to a solid form in said complementary grooves

2. A method of claim 1 wherein said panels are each of a composite which includes wood fibre material or at least included wood fibre material.

3. A method of claim 1 or 2 wherein said first panel is fixed prior to the positioning and fixing of the second panel.

4. A method of any one of the preceding claims wherein the fixing of each panel comprises or includes nailing and/or screwing into said joists.

5. A method of any one of the preceding claims wherein the panel to panel adhered and adhesive formed splined joint does not overlie nogs.

6. A method of any one of the preceding claims wherein said panels are rectangular and are grooved on two opposed sides only, such two opposed sides being normal to the run of the joists.

7. A method of any one of the preceding claims wherein said panels are rectangular and at least the two longer sides are grooved.

8. A method of any one of the preceding claims wherein those edges of panels to be adjacent the edges of other panels along a joist are ungrooved.

9. A method of any one of the preceding claims wherein adhesive is applied to at least one edge of fixed panels prior to abutment thereagainst of a yet to be fixed panel.

10. A method of any one of the preceding claims wherein the adhesive is of a solvent mastic type formulation with a synthetic rubber base.

11. A method of edgewise joining flooring panels which comprises fixing in place a first panel said panel having an edge provided with at least one groove, applying adhesive into said groove(s), and abutting a second panel provided with at least one groove complementary to that of said first panel in the plane of the first panel, so that there is an adhesive joint having



resistance in shear to relative vertical movement of the panel edges as well as a forming of a spline between the panels moulded at least in part by the said complementary said adhesive being of a type which assumes a shape retaining form sufficient to serve a spline function in addition to any adhesive function it may provide, and at least some adhesive has set to a solid form in said complementary grooves

04  
08  
09  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
2221  
2222

12. Flooring or a floor formed by a method of any one of the preceding claims.
13. A flooring panel which when used in a method of any one of claims 1 to 11, said panel being of a composite material including wood fibre or which included wood fibre as a raw material and having at least one grooved edge.
14. A flooring panel of claim 13 in the form of a rectangular or square sheet having a pair of opposite edges provided with at last one groove fully extensive with the length of each edge.
15. A panel of claim 14 wherein the groove is in a longer pair of edges.
16. A panel of claim 14 or 15 wherein said groove(s) is(are) centrally positioned on such edges.
17. A floor comprising a floor frame of primarily joists, and a plurality of abutting panels positioned on top of said floor frame to define the desired floor shape, at least part of each adjacent edge of adjacent panels which is substantially perpendicular to the joist axes is provided with a groove which complements a corresponding groove of the adjacent edge of the adjacent panel, a spline having been moulded in said complementary grooves during adhesive butting of said edges after adhesive has been applied to at least one of said edges, said adhesive being of a type which assumes a shape retaining form sufficient to serve a spline function in addition to any adhesive function it may provide, and at least some adhesive has set to a solid form in said complementary grooves.
18. A floor as claimed in claim 17 wherein said floor has been formed by a method as claimed in any one of claims 1 to 12.
19. A method of edgewise joining flooring panels substantially as hereinbefore described with reference to the accompanying drawings.
20. Floor panels substantially as hereinbefore described with reference to the accompanying drawings.
21. A floor constructed by a method of claim 19.








FIG. 1




FIG. 2




FIG. 3A

22 09 98 0213




FIG. 3B

2025 RELEASE UNDER E.O. 14176




FIG. 3C

2025 08 02 00 00 00




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6

FIG. 7




FIG. 8





FIG. 9







FIG. 11







FIG. 12

FIG. 13








FIG. 14




FIG. 15

FIG. 16




FIG. 17






FIG. 18FIG. 19

FIG. 20




FIG. 21





FIG. 22FIG. 23